



### Description

Tunable White. IP67\*, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable. PMMA LED lens. Factory installed LED circuit board with Tunable White Technology. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment.

Eco Step Dim® on request.

The optional installation blockout is recommended for mounting. To be ordered separately.

The luminaire is not suitable for permanent underwater operation and must be switched off in the event of flooding.

\* Additionally tested to IP66, IP67, IP68 0.1 bar 3h, up to

**Inground luminaires**

1 m depth according to DIN EN 60598 and IP69K/80°  
according to DIN EN 60529.

**Inground luminaires****Specifications****Material description**

Body	Marine-grade all aluminium construction. Anodized aluminium extrusion.
Lens	Safety glass lens; max. static load 3 tonnes
Colours	
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP67
Impact resistance	IK08

**Electrical description**

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DALI
Power factor	> 0.9
Surge protection	1/2 kV

**Additional information**

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	D (Light source)

**Options****Light distribution**

asymmetric, wallgrazer [A6]

**Colour temperature**

2200-6000K

**Nominal Watt**


0 W

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric, wallgrazer [A6] 	186-0380	LED-96/30W - 2200-6000 K	2658.2	33.5 W	80	6.00


**Electrical Accessories****Sealable junction box**

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19




**Optical Accessories****Honeycomb louvre**

Description	Part ID	C1	H1
IW for ETV130	186-0295	898	30




**Mounting Accessories****Installation blockout, Type I**

Description	Part ID	A	C1	D1	D2	Weight(kg)
BEV130-I-1/927 (1 luminaire)	186-0310	975	160	55	120	4.70




BEV130-I-2/927 (2 luminaires)	186-0311	1904	160	55	120	9
-------------------------------	----------	------	-----	----	-----	---



**Inground luminaires**

Description	Part ID	A	C1	D1	D2	Weight(kg)
BEV130-I-3/927 (3 luminaires)	186-0312	2833	160	55	120	13.20



BEV130-I-4/927 (4 luminaires)	186-0313	3762	160	55	120	17.50
-------------------------------	----------	------	-----	----	-----	-------

