


Inground Luminaires**Description**

Column Grazer.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. 0-10V Dimming. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Inground Luminaires

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Inground Luminaires**Specifications****Material description**

Body	Marine-grade all aluminum construction. Anodized aluminum extrusion.
Lens	Safety glass lens; max. load 3 tonnes
Colors	
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP69K - HIGHEST PROTECTION RATING AVAILABLE
Impact resistance	IK08

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Electronic converter with 0-10V interface
Power factor	> 0.9

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.


Inground Luminaires**Options****Light distribution****Color temperature****Nominal Watt**

asymmetric, wallgrazer [A6]



3000 K

0 W



4000 K




2700 K

Inground Luminaires**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
asymmetric, wallgrazer [A6]	186-0374	LED-64/40W / 225 mA - 3000 K	4382.8	44 W	80	17.00
	186-0375	LED-64/40W / 225 mA - 4000 K	4382.8	44 W	80	17.00
	186-0416	LED-64/40W / 225 mA - 2700 K	4382.8	44 W	80	16.53


Inground Luminaires**Electrical Accessories****Sealable junction box**

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	\emptyset 0.39	\emptyset 0.47 - 0.75



Inground Luminaires**Optical Accessories****Honeycomb louvre**

Description	Part ID	C1	H1
IW for ETV140	186-0296	47.16	1.18




Inground Luminaires


Mounting Accessories

Installation breakout, Type I

Description	Part ID	Additional information	A	C1	D1	D2	Weight(lb)
BEV140-I-1/1227 (1 luminaire)	186-0314	Blockout Accessory Depth (C1) to 6.3".	50.2	6.30	2.13	4.72	13.45 lbs




BEV140-I-2/1227 (2 luminaires)	186-0315	Blockout Accessory Depth (C1) to 6.3".	98.58	6.30	2.13	4.72	25.79 lbs
--------------------------------	----------	--	-------	------	------	------	-----------



Inground Luminaires

Description	Part ID	Additional information	A	C1	D1	D2	Weight(lb)
BEV140-I-3/1227 (3 luminaires)	186-0316	Blockout Accessory Depth (C1) to 6.3".	146.97	6.30	2.13	4.72	38.36 lbs



BEV140-I-4/1227 (4 luminaires)	186-0317	Blockout Accessory Depth (C1) to 6.3".	195.35	6.30	2.13	4.72	50.68
--------------------------------	----------	--	--------	------	------	------	-------

