

#### Description

Tunable White.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. Tunable White technology. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.



## **Inground Luminaires**

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



#### **Inground Luminaires**

## **Specifications**

## **Material description**

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens; max. static load 3 tonnes

Colors

Gasket Silicone CCG® Controlled Compression Gasket
Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK08

#### **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. DMX Dimmable.

Driver / Ballast Integral DMX electronic converter

Power factor > 0.9

#### **Additional information**

Lifetime  $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ 

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



## **Inground Luminaires**

# **Options Light distribution**



symmetric linear, wide beam [LW]



symmetric linear, medium beam [LM]



symmetric linear, narrow beam [LN]



symmetric linear, very narrow beam [LVN]



asymmetric linear, wallwash [LA10]

## **Color temperature Nominal Watt**

2200-6000K 0 W



# **Configurations**


Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
asymmetric linear, wallwash [LA10]	186-0334	LED-96/30W - 2200-6000 K	2733.1	33.5 W	80	13.23
symmetric linear, medium beam [LM]	186-0336	LED-96/30W - 2200-6000 K	2853.8	33.5 W	80	13.23
symmetric linear, narrow beam [LN]	186-0337	LED-96/30W - 2200-6000 K	2801.7	33.5 W	80	13.23
symmetric linear, very narrow beam [LVN]	186-0333	LED-96/30W - 2200-6000 K	3207.9	33.5 W	80	13.23
symmetric linear, wide beam [LW]	186-0335	LED-96/30W - 2200-6000 K	2554.3	33.5 W	80	13.23



## **Electrical Accessories**

## Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75






## **Inground Luminaires**

# **Optical Accessories**

## **Honeycomb louvre**

Description	Part ID	C1	H1
IW for ETV130	186-0295	35.35	1.18



# **Mounting Accessories**


## Installation blockout, Type I

Description	Part ID	А	C1	D1	D2	Weight (lb)
BEV130-I-1/927 (1 luminaire)	186-0310	38.38"	6.30	2.13	4.72	10.36 lbs

BEV130-I-2/927 (2 luminaires) 186-0311 74.96 6.30 2.13 4.72 19.84



Description	Part ID	А	C1	D1	D2	Weight (lb)
BEV130-I-3/927 (3 luminaires)	186-0312	111.54	6.30	2.13	4.72	29.10 lbs



BEV130-I-4/927 (4 luminaires) 186-0313 148.11 6.30 2.13 4.72 38.58

