

Description

IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens.

Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 3.0 m. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.

Maximum one internal optical accessory possible. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	<div style="display: flex; flex-direction: column; gap: 5px;"> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: black; margin-right: 5px;"></div> RAL9004 Signal black </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #808080; margin-right: 5px;"></div> RAL9007 Grey aluminium </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #404040; margin-right: 5px;"></div> RAL7016 Anthracite grey </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #e0e0e0; margin-right: 5px;"></div> RAL9016 Traffic white </div> </div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Windage	0.065 ft ²

Electrical description

Driver / Ballast	Electronic control gear in separate gear box (constant current), prewired
Power factor	> 0.9

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution



symmetric, wide beam [B]



symmetric, medium beam [M]



symmetric, narrow beam [E]



symmetric, very narrow beam [EE]



symmetric, very narrow beam, sharp cut-off [EES]

Colour temperature



2700 K



3000 K








4000 K

Nominal Watt


0 W

Configurations


Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	139-2438	LED-1/6W / 500 mA - 2700 K	544.8	7.5 W	80	0.50
	139-2439	LED-1/6W / 500 mA - 3000 K	544.8	7.5 W	80	0.50
	139-2440	LED-1/6W / 500 mA - 4000 K	585.5	7.5 W	80	0.50
symmetric, narrow beam [E] 	139-2441	LED-1/6W / 500 mA - 2700 K	567.7	7.5 W	80	0.50
	139-2442	LED-1/6W / 500 mA - 3000 K	567.7	7.5 W	80	0.50
	139-2443	LED-1/6W / 500 mA - 4000 K	610.1	7.5 W	80	0.50
symmetric, very narrow beam [EE] 	139-2444	LED-1/6W / 500 mA - 2700 K	568.2	7.5 W	80	0.50
	139-2445	LED-1/6W / 500 mA - 3000 K	568.2	7.5 W	80	0.50
	139-2446	LED-1/6W / 500 mA - 4000 K	610.6	7.5 W	80	0.50
symmetric, very narrow beam, sharp cut-off [EES] 	139-2447	LED-1/6W / 500 mA - 2700 K	516.6	7.5 W	80	0.50
	139-2448	LED-1/6W / 500 mA - 3000 K	516.6	7.5 W	80	0.50
	139-2449	LED-1/6W / 500 mA - 4000 K	558.6	7.5 W	80	0.50
symmetric, wide beam [B] 	139-2435	LED-1/6W / 500 mA - 2700 K	518.4	7.5 W	80	0.50
	139-2436	LED-1/6W / 500 mA - 3000 K	518.4	7.5 W	80	0.50
	139-2437	LED-1/6W / 500 mA - 4000 K	557.1	7.5 W	80	0.50

Optical Accessories**Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	139-2453	41.8

**Honeycomb louvre**


Description	Part ID	C1
Honeycomb louvre IW	139-2454	48



Projectors


Glare shield

Description	Part ID	A	C1
Glare shield ES	139-2455	59.5	75



Snoot


Description	Part ID	A	C1
Snoot ET	139-2456	60	75




Electrical Accessories

Gear box

Description	Part ID	A	B	C1	C2	Weight (kg)
GB200 R130x80 gear box (small) DALI	139-2555	50	80	159	130	0.30




GB200 R200x120 gear box (medium) DALI	139-2622	75	120	229	200	
--	----------	----	-----	-----	-----	--



Projectors


Description	Part ID	A	B	C1	C2	Weight (kg)
GB200 R230x140 gear box (large) SP10 DALI	139-2621	95	140	259	230	



Mounting Accessories

Junction box

Description	Part ID	A	B	C1	C2
Junction box JB200 R82	139-2590	55	82	140	80



Pole clamp PC - Rotatable

Description	Part ID	D1	Weight (kg)
PC2 114-133/60 Pole clamp, double (Ø 114-133)	139-2709	114-133	1.40

