


**Description**

IP66, Class I. Class II on request. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG[®] Controlled Compression Gasket. PMMA main lens. The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter. DALI. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised indirect optics for superior illumination and glare control.

Pole mounted

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	PMMA
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE+Primer
Windage	0.205 m ²

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Power factor	> 0.9
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.

Additional information

Lifetime	Ta=40° L70B50 > 50000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Pole mounted

Options

Light distribution

Colour temperature

Nominal Watt



-  controlled symmetric distribution [C50]
-  symmetric distribution [C60]
-  rectangular [R50]

-  2700 K
-  3000 K
-  4000 K

24 W

Pole mounted

Configurations


Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
controlled symmetric distribution [C50] 	115-1754	LED-FT-24W / 700 mA - 2700 K	3312.3	27 W	80	9.90
	115-1755	LED-FT-24W / 700 mA - 3000 K	3451.4	27 W	80	9.90
	115-1756	LED-FT-24W / 700 mA - 4000 K	3598.6	27 W	80	9.90
	115-1757	LED-FT-37W / 700 mA - 2700 K	5025.8	42 W	80	9.90
	115-1758	LED-FT-37W / 700 mA - 3000 K	5177.1	42 W	80	9.90
	115-1759	LED-FT-37W / 700 mA - 4000 K	5475.6	42 W	80	9.90
rectangular [R50] 	115-1897	LED-FT-24W / 700 mA - 3000 K	3335	27 W	80	9.90
	115-1898	LED-FT-24W / 700 mA - 4000 K	3477.3	27 W	80	9.90
	115-1899	LED-FT-24W / 700 mA - 2700 K	3200.7	27 W	80	9.90
	115-1900	LED-FT-37W / 700 mA - 3000 K	5002.5	42 W	80	9.90
	115-1901	LED-FT-37W / 700 mA - 4000 K	5291	42 W	80	9.90
	115-1902	LED-FT-37W / 700 mA - 2700 K	4856.3	42 W	80	9.90
symmetric distribution [C60] 	115-1760	LED-FT-24W / 700 mA - 2700 K	3033.6	27 W	80	9.90
	115-1761	LED-FT-24W / 700 mA - 3000 K	3160.9	27 W	80	9.90
	115-1762	LED-FT-24W / 700 mA - 4000 K	3295.7	27 W	80	9.90
	115-1763	LED-FT-37W / 700 mA - 2700 K	4602.8	42 W	80	9.90
	115-1764	LED-FT-37W / 700 mA - 3000 K	4741.3	42 W	80	9.90
	115-1765	LED-FT-37W / 700 mA - 4000 K	5014.7	42 W	80	9.90

Pole mounted

Optical Accessories

Light shield


Description	Part ID	H1
LS180-[C60]	159-0321	120



Mounting Accessories

Wall and pole brackets RZ

Description	Part ID	C1	D1	D2	D × L1	M1	Weight (kg)
RZ0-400 Wall bracket, single	115-1324	277	231	195	76 x 80	12	3.50



RZ2-400 Pole bracket, double	115-1323	258			76 x 100	4.90
------------------------------	----------	-----	--	--	----------	------

