**Description**

Tunable white. IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

**Specifications****Material description**

Body	Marine-grade, all-aluminium construction. Pole section features anodised aluminium core
Lens	Polycarbonate main lens, UV-stabilised
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK10
Corrosion resistance	5CE

**Electrical description**


Driver / Ballast	Integral EC electronic converter, DALI
Surge protection	10/10kV

**Additional information**

Lifetime	Ta=25° L70B50>50000h
ENERGY EFFICIENCY	F (Light source)
CLASS	

**Options****Light distribution**

symmetric [C70]



asymmetric, side throw beam [S60]


**Colour temperature**

2700-5000K

**Nominal Watt**

0 W

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric, side throw beam [S60]	115-9813	LED-10W/300 mA - 2700-5000K	567.2	12 W	80	8.00
						
symmetric [C70]	115-9810	LED-10W/300 mA - 2700-5000K	699.9	12 W	80	8.00
						

**Mounting Accessories****Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	Weight (kg)
Planted root ESZ4	300-9090	55	45	70	100	400	350	3.50

