



#### **Description**

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.



# **Specifications Material description**

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium
RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

#### **Electrical description**

Driver / Ballast DALI

#### **Additional information**

#### **DAS140-PM TW LED**



#### **Ceiling luminaires**

# **Options Light distribution**

Colour temperature No

**Nominal Watt** 



symmetric, medium beam [M]

2200-6000K

.

0 W



symmetric, wide beam [B]



symmetric, narrow beam [E]

#### **DAS140-PM TW LED**



## **Ceiling luminaires**

# **Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M]	134-2319	LED-24/42W / 325 mA - 2200-6000K	4605.8	51 W	80	5.50
symmetric, narrow beam [E]	134-2320	LED-24/42W / 325 mA - 2200-6000K	4789.4	51 W	80	5.50
symmetric, wide beam [B]	134-2318	LED-24/42W / 325 mA - 2200-6000K	4340.7	51 W	80	5.50



# **Optical Accessories**

## **Linear spread lens**

Description	Part ID
IO-180-DAC140-LED	134-2064



#### Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	



#### **DAS140-PM TW LED**



## **Ceiling luminaires**

## **Honeycomb louvre**

Description	Part ID	
IW-DA_140-LED	134-2066	





# **Mounting Accessories**

## Adaptor for side conduit entry

Description	Part ID	Α	C1
DA14 Adaptor for DAC140/DAS140-	134-2109	31	195
PM			

