
Ceiling Luminaires





Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 1.5 - 5 ft., to be specified at time at ordering. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DALI interface. The luminaire is factory-sealed and does not need to be opened during installation.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)



Ceiling Luminaires

Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Driver / Ballast DALI

Additional information

Listings Contact WE-EF USA for ETL/UL certification status.



Ceiling Luminaires

Options Light distribution

Color temperature

Nominal Watt

symmetric, medium beam [M]

2200-6000K

0 W

symmetric, wide beam [W]



symmetric, narrow beam [E]



Ceiling Luminaires

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
symmetric, medium beam [M]	134-2319	LED-24/42W / 325 mA - 2200-6000K	4605.8	51 W	80	5.50
symmetric, narrow beam [E]	134-2320	LED-24/42W / 325 mA - 2200-6000K	4789.4	51 W	80	5.50
symmetric, wide beam [W]	134-2318	LED-24/42W / 325 mA - 2200-6000K	4340.7	51 W	80	5.50



Ceiling Luminaires

Optical Accessories

Linear spread lens

Description	Part ID	
IO-180-DAC140-LED	134-2064	





Ceiling Luminaires


Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	



Honeycomb louvre

Description	Part ID	
IW-DA_140-LED	134-2066	





Ceiling Luminaires

Mounting Accessories

Adaptor for side conduit entry

Description	Part ID	Α	C1
DA14 Adaptor for DAC140/DAS140-	134-2109	1.20	7.70
PM			

