


Floodlights



Description

Profile Projector [FP] for framing applications, polygon shape. Spherical and aspherical, double flat convex lens system.



IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.

Floodlights**Specifications****Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors

	RAL9004 Black
	RAL9007 Grey Metallic
	RAL9016 White
	RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners Eingebauter Flanschstecker M8 x 1,5. Anschlussleitung 3 m

Ingress protection IP66

Impact resistance IK07

Corrosion resistance 5CE

Windage 0.11 ft²

Electrical description

Driver / Ballast DALI

Power factor > 0.9

Additional information

Lifetime Ta=25°/40° L90B10 > 90000h

Floodlights**Options****Light distribution**

symmetric Framing-Projector [FP] - min aperture angle



symmetric Framing-Projector [FP] - max aperture angle

Color temperature

2700 K

0 W



3000 K




4000 K

Floodlights**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
symmetric Framing-Projector [FP] - max aperture angle 	139-2752_max	LED-1/6W / 500 mA - 2700 K	373.3	7.5 W	80	1.87
	139-2753_max	LED-1/6W / 500 mA - 3000 K	373.3	7.5 W	80	1.87
	139-2754_max	LED-1/6W / 500 mA - 4000 K	401.1	7.5 W	80	1.87
symmetric Framing-Projector [FP] - min aperture angle 	139-2752_min	LED-1/6W / 500 mA - 2700 K	394.6	7.5 W	80	1.87
	139-2753_min	LED-1/6W / 500 mA - 3000 K	394.6	7.5 W	80	1.87
	139-2754_min	LED-1/6W / 500 mA - 4000 K	424	7.5 W	80	1.87


Floodlights**Mounting Accessories****Ground spike EF**

Description	Part ID	H1	Weight (lb)
EF1-M18 Ground spike	310-0045	10.70	0.80



Floodlights**Junction box**

Description	Part ID	A	B	C1	C2
JB200 R82 Junction box	139-2590	2.17	3.23	5.51	3.15



Floodlights**Electrical Accessories****Gear box**

Description	Part ID	A	B	C1	C2
FLC201 Remote Gear Box	139-6977	3	4.7	9	7.9

