




Description

Profile Projector [FP] for framing applications, polygon shape. Spherical and aspherical, double flat convex lens system.

IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.



Floodlights

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colors	<div> <div></div> <div>RAL9004 Black</div> </div> <div> <div></div> <div>RAL9007 Grey Metallic</div> </div> <div> <div></div> <div>RAL9016 White</div> </div> <div> <div></div> <div>RAL8019 Dark Bronze</div> </div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	Eingebauter Flanschstecker M8 x 1,5. Anschlussleitung 3 m
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Windage	0.11 ft ²

Electrical description

Driver / Ballast	DALI
Power factor	> 0.9



Additional information




Lifetime	Ta=25°/40° L90B10 > 90000h
----------	----------------------------

Floodlights

Options



Light distribution

- symmetric Framing-Projector [FP] - min aperture angle
- symmetric Framing-Projector [FP] - max aperture angle

Color temperature	Nominal Watt
 2700 K	0 W
 3000 K	
 4000 K	

Floodlights


Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
symmetric Framing-Projector [FP] - max aperture angle 	139-2752_max	LED-1/6W / 500 mA - 2700 K	373.3	7.5 W	80	1.87
	139-2753_max	LED-1/6W / 500 mA - 3000 K	373.3	7.5 W	80	1.87
	139-2754_max	LED-1/6W / 500 mA - 4000 K	401.1	7.5 W	80	1.87
symmetric Framing-Projector [FP] - min aperture angle 	139-2752_min	LED-1/6W / 500 mA - 2700 K	394.6	7.5 W	80	1.87
	139-2753_min	LED-1/6W / 500 mA - 3000 K	394.6	7.5 W	80	1.87
	139-2754_min	LED-1/6W / 500 mA - 4000 K	424	7.5 W	80	1.87

Mounting Accessories

Ground spike EF


Description	Part ID	H1	Weight (lb)
EF1-M18 Ground spike	310-0045	10.70	0.80



Floodlights

Junction box

Description	Part ID	A	B	C1	C2
JB200 R82 Junction box	139-2590	2.17	3.23	5.51	3.15



Electrical Accessories

Gear box

Description	Part ID	A	B	C1	C2
FLC201 Remote Gear Box	139-6977	3	4.7	9	7.9

