
Ceiling luminaires







Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Pendelum rod 0.5 - 1.5 m can be selected in 0.1 m increments. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering



Ceiling luminaires

Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Driver / Ballast Integral EC electronic converter

Power factor >0.9

Additional information

Lifetime $T_a=40^{\circ} L90B10 > 90000h$

we-ef

Ceiling luminaires

Options

Light distribution Colour temperature Nominal Watt



Ceiling luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		



Ceiling luminaires

Optical Accessories

Linear spread lens

Description	Part ID	
IO-180-DAC110	134-2104	



Honeycomb louvre

Description	Part ID	
IW-DAC110	134-2105	



WE-EF LIGHTING Pty Ltd



Ceiling luminaires

Wallwash lens

Description	Part ID	C1		
IO-20-WW-DAC110-LED	134-2361	76		

