

Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Pendulum rod 0.5 - 1.5 m can be selected in 0.1 m increments. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

Specifications**Material description**

Body	Marine-grade, all aluminium construction
Lens	Safety glass lens
Colours	<div><div></div> RAL9004 Signal black</div> <div><div></div> RAL9006 White aluminium</div> <div><div></div> RAL9007 Grey aluminium</div> <div><div></div> RAL7016 Anthracite grey</div> <div><div></div> RAL9016 Traffic white</div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Power factor	>0.9
Surge protection	1/2 kV (optional SP10)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	C-D (Light source)





DAS120-PR LED

Ceiling luminaires






Options





Light distribution

	symmetric, wide beam [B]
	symmetric, medium beam [M]
	symmetric, very narrow beam [EE]
	symmetric, very narrow beam, sharp cut-off [EES]

Colour temperature Nominal Watt

	2700 K	0 W
	3000 K	
	4000 K	


Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	134-2416	LED-12/24W / 700 mA - 2700 K	2875.2	27 W	80	3.60
	134-2417	LED-12/24W / 700 mA - 3000 K	3088.2	27 W	80	3.60
	134-2418	LED-12/24W / 700 mA - 4000 K	3301.2	27 W	80	3.60
symmetric, very narrow beam [EE] 	134-2419	LED-12/24W / 700 mA - 2700 K	2880.3	27 W	80	3.60
	134-2420	LED-12/24W / 700 mA - 3000 K	3093.7	27 W	80	3.60
	134-2421	LED-12/24W / 700 mA - 4000 K	3307	27 W	80	3.60
symmetric, very narrow beam, sharp cut-off [EES] 	134-2422	LED-12/24W / 700 mA - 2700 K	2947.4	27 W	80	3.60
	134-2423	LED-12/24W / 700 mA - 3000 K	3165.7	27 W	80	3.60
	134-2424	LED-12/24W / 700 mA - 4000 K	3384	27 W	80	3.60
symmetric, wide beam [B] 	134-2413	LED-12/24W / 700 mA - 2700 K	2382.4	27 W	80	3.60
	134-2414	LED-12/24W / 700 mA - 3000 K	2558.9	27 W	80	3.60
	134-2415	LED-12/24W / 700 mA - 4000 K	2735.4	27 W	80	3.60

Optical Accessories

Linear spread lens


Description	Part ID	Additional information	C1
IO-180-DAC120-LED	134-2000	Broadens light distribution in one plane only. Ideally suitable for [M][EE][EES]. Does not fit in combination with [B] lens. A maximum of one internal optical accessory. Internal component, factory installed.	130



Ceiling luminaires

Honeycomb louvre

Description	Part ID	Additional information	C1
IW-DAC120-LED	134-2002	Honeycomb louvre, matt black Teflon® coated. For luminaires equipped with [B] [M] light distribution. A maximum of one internal optical accessory. Internal component, factory installed.	103



Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC120-LED	134-2001	92

