
#### **Ceiling luminaires**







#### **Description**

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Pendelum rod 0.5 - 1.5 m can be selected in 0.1 m increments. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.



#### **Ceiling luminaires**

# **Specifications Material description**

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

#### **Electrical description**

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Power factor >0.9

#### **Additional information**

Lifetime Ta=40° L90B10 > 90000h

we-ef

**Ceiling luminaires** 

**Options** 

Light distribution Colour temperature Nominal Watt



## **Ceiling luminaires**

# **Configurations**

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		



#### **Ceiling luminaires**

# **Optical Accessories**

## **Linear spread lens**

Description	Part ID	
IO-180-DAC140-LED	134-2064	



#### Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	





## **Ceiling luminaires**

#### Honeycomb louvre

Description	Part ID
IW-DA_140-LED	134-2066

