
# we-ef

#### **Street and Area Lighting**





#### **Description**

RGBW/RGBA Colour Changer. IP66. Class I. IK08. Marinegrade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DMX interface. CADoptimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.



#### **Street and Area Lighting**

# Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens PMMA RFC® Reflection Free Contour technology

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK08
Corrosion resistance 5CE

Windage 0.24 m<sup>2</sup>

## **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter. DMX

Power factor > 0.9

#### **Additional information**

Lifetime Ta=25°/40° L90B10 > 90000h

we-ef

**Street and Area Lighting** 

**Options** 

Light distribution Color temperature Nominal Watt



## **Street and Area Lighting**

# **Configurations**

Light distribution	Part ID	Light source	Delivered	Rated input	CRI	Weight (lb)
			lumens	power		



# **Street and Area Lighting**

#### Control

## **DMX Wireless Antenna**

Description	Part ID	
Antenna RF 5dB	430-0036	
Antenna RF1.8dB	430-0018	