

### Description





Solar (ISP - integrated solar panel, fully independent). IP66, Class III. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. CCG® Controlled Compression Gasket. Non-reflective flat safety glass cover, hinged. Integral D4i-certified electronic LED driver in Zhaga format. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed WE-EF LED circuit board (Zhaga Book 15 compliant). The luminaire is factory-sealed and does not need to be opened during installation. Flush installation of the solar module with the housing for a clean finish. Alignment of the solar panel only in combination with the luminaire Can be used as post top or side entry version. Specification at time of order is recommended. Spigot Ø 3" x 4" .

Contact WE-EF direct or your local WE-EF sales representative for an individual solution designed to precisely meet your needs. Photometric files (IES, LDT) for light distributions [S70] A61] [P66] with Backlight Shield on request.

## Street and Area Lighting

## Specifications

## Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Non-reflective safety glass lens
Colors	 RAL9004 Black  RAL9007 Grey Metallic  RAL9016 White  RAL8019 Dark Bronze
Gasket	CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE
Windage	0.191 m <sup>2</sup>

## Electrical description








Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Power factor	> 0.9
Surge protection	6/6kV, optional 10kV

## Additional information

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	C-D (Light source)





Street and Area Lighting

Options

Light distribution	Color temperature	Nominal Watt
 [S70] Type II Short	 2700 K	11 W 24 W
 rectangular, side throw [R60]	 1850 K	
 [A61] Type IV Very Short	 3000 K	
 [P66] Type II Medium		

## Street and Area Lighting


## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
[A61] Type IV Very Short 	102-0808	LED-24/11W / 160 mA - 2700K	1533.7	12 W	80	15.40
	102-0812	LED-24/7,5W / 160 mA - Amber	473.2	8 W	80	15.40
	102-0816	LED-24/11W / 160 mA - PCA	1134.9	12 W	80	15.40
	102-1000	LED-24/11W / 160 mA - 3000K	1638.8	12 W	80	15.40
[P66] Type II Medium 	102-0809	LED-24/11W / 160 mA - 2700K	1550.6	12 W	80	15.40
	102-0813	LED-24/7,5W / 160 mA - Amber	478.5	8 W	80	15.40
	102-0817	LED-24/11W / 160 mA - PCA	1147.5	12 W	80	15.40
	102-1001	LED-24/11W / 160 mA - 3000K	1657	12 W	80	15.40
[S70] Type II Short 	102-0806	LED-24/11W / 160 mA - 2700K	1659.7	12 W	80	15.40
	102-0810	LED-24/7,5W / 160 mA - Amber	512.1	8 W	80	15.40
	102-0814	LED-24/11W / 160 mA - PCA	1228.2	12 W	80	15.40
	102-0998	LED-24/11W / 160 mA - 3000K	1773.5	12 W	80	15.40
rectangular, side throw [R60] 	102-0807	LED-24/11W / 160 mA - 2700K	1529.2	12 W	80	15.40
	102-0811	LED-24/7,5W / 160 mA - Amber	471.9	8 W	80	15.40
	102-0815	LED-24/11W / 160 mA - PCA	1131.6	12 W	80	15.40
	102-0999	LED-24/11W / 160 mA - 3000K	1634.1	12 W	80	15.40

Mounting Accessories

Adaptor

Description	Part ID
Adaptor AFL100	102-0392



Optical Accessories

Backlight shield

Description	Part ID	Additional information
LS180	430-0029	Glare Shield for backlight spill. Glare Shield factory-installed or available as retrofit kit. Suitable for [S61][S65][S66][S70][S71][R60][R61][P66][Q66][A61] lenses. Must be specified at time of ordering.

