
we-ef

Inground luminaires





Description

IP68 (up to 10m), 12V/Class III. IK09. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1.5 m of flexible PVC free cable. IP68 in-line connector facilitates easy removal for off-site lamp replacement.

Factory installed circuit board in either white, red, green, blue or RGB. LED boards can be easily removed for upgrading.

Luminaire requires installation blockout. To be ordered separately.

Use in freshwater is allowed. The use in contaminated water, salt water/sea water or swimming pools is not permitted.



Inground luminaires

Specifications

Material description

Body Stainless steel construcion

Lens Safety glass lens; max. load 5 tonnes

Colours Stainless Steel

Fasteners PCS polymer coated stainless steel

Ingress protection IP68 up to 10 m

Impact resistance IK09

Electrical description

Driver / Ballast EC electronic converter required. To be ordered separately.

Additional information

Lifetime Ta=40° L90B10 > 90000h

we-ef

Inground luminaires

Options

Light distribution Colour temperature Nominal Watt



Inground luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		




Inground luminaires

Electrical Accessories


Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19



Main converter

Description
TVE-DC 12 V/12 W





Inground luminaires

cription Part ID A	A B C1
C 12 V/48 W 400-0309 89	39 59

