
## we-ef

#### **Inground luminaires**





#### **Description**

IP68 (up to 10m), 12V/Class III. IK09. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1.5 m of flexible PVC free cable. IP68 in-line connector facilitates easy removal for off-site lamp replacement.

Factory installed circuit board in either white, red, green, blue or RGB. LED boards can be easily removed for upgrading.

Luminaire requires installation blockout. To be ordered separately.

Use in freshwater is allowed. The use in contaminated water, salt water/sea water or swimming pools is not permitted.



#### **Inground luminaires**

## **Specifications**

## **Material description**

Body Stainless steel construcion

Lens Safety glass lens; max. load 5 tonnes

Colours Stainless Steel

Fasteners PCS polymer coated stainless steel

Ingress protection IP68 up to 10 m

Impact resistance IK09

#### **Electrical description**

Driver / Ballast EC electronic converter required. To be ordered separately.

#### **Additional information**

Lifetime Ta=25° L90B10 > 90000h

# we-ef

**Inground luminaires** 

**Options** 

Light distribution Colour temperature Nominal Watt



## **Inground luminaires**

## **Configurations**

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		



## **Inground luminaires**

## **Mounting Accessories**


#### Installation cover

Description	Part ID	C1
Installation cover BE	185-1850	65



## Installation blockout

Description	Part ID	D1	D2	H1	Weight (kg)	D	Н
Blockout, Plastic	185-1855	65	95	120	0.30	65/95	120






### **Inground luminaires**

### **Electrical Accessories**

#### Main converter

Description	Part ID	Α	В	C1
Transformer DC 12 V/12 W	400-0302	89	59	54



Transformer DC 12 V/48 W	400-0309	89	59	72

