


Wall luminaires recessed





#### Description

IP55, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Stainless steel mounting claws. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Integral EC Electronic convertor. High efficiency LEDs in 3000 K or 4000 K. Optional 2200 K version available. To be specified at time of ordering.

Optional pre-installation blockout is recommended for mounting in concrete.

#### Wall luminaires recessed

Specifications Material description					
Body	Marine-grade, all-aluminium construction				
Colours	RAL9004 Signal blackRAL9006 White aluminiumRAL9007 Grey aluminium				
Gasket	Silicone rubber gasket				
Ingress protection	IP55				
Impact resistance	IK10				

## **Electrical description**

5CE

Corrosion resistance

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter

### **Additional information**

Lifetime

Ta=40° L80B10 > 54000h

we-ef



Wall luminaires recessed

Options

Light distribution Colour temperature Nominal Watt

WE-EF LIGHTING Pty Ltd 47 Tarnard Drive, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499 info.australia@we-ef.com - https://we-ef.com/aus Subject to technical changes and errors. - Generated on 08/06/2025 we-ef







# Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		