




#### Wall luminaires recessed





#### **Description**

IP55, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Stainless steel mounting claws. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Integral EC Electronic convertor. High efficiency LEDs in 3000 K or 4000 K.

Special version of STG features a polished stainless steel frame.

Optional pre-installation blockout is recommended for mounting in concrete.



#### Wall luminaires recessed

# **Specifications**

## **Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Polycarbonate lens

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

#### **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

#### **Additional information**

Lifetime Ta=40° L80B10 > 54000h



Wall luminaires recessed

**Options** 

Light distribution Colour temperature Nominal Watt



## Wall luminaires recessed

# **Configurations**

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		