
we-ef

Wall luminaires recessed





Description

IP55, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Stainless steel mounting claws. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Integral EC Electronic convertor. High efficiency LEDs in 3000 K or 4000 K.

Special version of STO features a polished stainless steel frame.

Optional pre-installation blockout is recommended for mounting in concrete.

STO209 LED Stainless steel



Wall luminaires recessed

Specifications

Material description

Body Marine-grade, die-cast aluminium alloy

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Lifetime Ta=40° L80B10 > 54000h

STO209 LED Stainless steel



Wall luminaires recessed

Options

Light distribution Colour temperature Nominal Watt

STO209 LED Stainless steel



Wall luminaires recessed

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		