


**Description**

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Non-reflecting safety glass lens, hinged with safety switch. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation. Optional 2200 K version available. To be specified at time of ordering.

Includes cable connector, for cable 6-12 mm. Cable inclination angle: Maximum 10°.

Catenary luminaires**Specifications****Material description**

Body	Marine-grade, die-cast aluminium alloy
Lens	Non-reflecting safety glass lens, hinged
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE+Primer
Windage	0.062 m ²

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Power factor	< 0.9

Additional information

Lifetime	T _a =40° L90B10 > 90000h
----------	-------------------------------------

RFS530 LED

Catenary luminaires

Options

Light distribution



asymmetric, side throw [S60]



asymmetric, side throw [S65]



asymmetric, side throw [S70]

Colour temperature



4000 K



3000 K



2700 K

Nominal Watt




59 W

18 W

15 W

29 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric, side throw [S60] 	111-0697	LED-24/24W/24W / 700 mA - 4000 K	6498.3	54 W	80	11.90
	111-0706	LED-12/6W/6W / 350 mA - 3000 K	1705.8	14 W	80	11.60
	111-0707	LED-12/6W6W / 350 mA - 4000 K	1870.8	14 W	80	11.60
	111-0708	LED-24/12W/12W / 350 mA - 3000 K	3411.5	27 W	80	11.90
	111-0709	LED-24/12W/12W / 350 mA - 4000 K	3741.7	27 W	80	11.90
	111-0718	LED-12/12W/12W / 700 mA - 3000 K	3039.5	27 W	80	11.60
	111-0719	LED-12/12W/12W / 700 mA - 4000 K	3249.2	27 W	80	11.60
	111-0720	LED-24/24W/24W / 700 mA - 3000 K	6079.1	54 W	80	11.90
	111-1088	LED-12/6W/6W / 350 mA - 2700 K	1595.7	14 W	80	11.60
	111-1089	LED-12/12W/12W / 700 mA - 2700 K	2829.9	27 W	80	11.60
	111-1090	LED-24/12W/12W / 350 mA - 2700 K	3191.4	27 W	80	11.90
	111-1091	LED-24/24W/24W / 700 mA - 2700 K	5659.8	54 W	80	11.90
asymmetric, side throw [S65] 	111-0710	LED-12/6W/6W / 350 mA - 3000 K	1690.2	14 W	80	11.60
	111-0711	LED-12/6W6W / 350 mA - 4000 K	1853.8	14 W	80	11.60
	111-0712	LED-24/12W/12W / 350 mA - 3000 K	3380.4	27 W	80	11.90
	111-0713	LED-24/12W/12W / 350 mA - 4000 K	3707.5	27 W	80	11.90
	111-0721	LED-12/12W/12W / 700 mA - 3000 K	3011.8	27 W	80	11.60
	111-0722	LED-12/12W/12W / 700 mA - 4000 K	3219.5	27 W	80	11.60
	111-0723	LED-24/24W/24W / 700 mA - 3000 K	6023.6	54 W	80	11.90
	111-0724	LED-24/24W/24W / 700 mA - 4000 K	6439	54 W	80	11.90
	111-1092	LED-12/6W/6W / 350 mA - 2700 K	1581.1	14 W	80	11.60
	111-1093	LED-12/12W/12W / 700 mA - 2700 K	2804.1	27 W	80	11.60
	111-1094	LED-24/12W/12W / 350 mA - 2700 K	3162.3	27 W	80	11.90
	111-1095	LED-24/24W/24W / 700 mA - 2700 K	5608.1	54 W	80	11.90
asymmetric, side throw [S70] 	111-0714	LED-12/6W/6W / 350 mA - 3000 K	1616.2	14 W	80	11.60
	111-0715	LED-12/6W6W / 350 mA - 4000 K	1772.6	14 W	80	11.60
	111-0716	LED-24/12W/12W / 350 mA - 3000 K	3232.4	27 W	80	11.90
	111-0717	LED-24/12W/12W / 350 mA - 4000 K	3545.2	27 W	80	11.90
	111-0725	LED-12/12W/12W / 700 mA - 3000 K	2879.9	27 W	80	11.60
	111-0726	LED-12/12W/12W / 700 mA - 4000 K	3078.5	27 W	80	11.60
	111-0727	LED-24/24W/24W / 700 mA - 3000 K	5759.8	54 W	80	11.90
	111-0728	LED-24/24W/24W / 700 mA - 4000 K	6157	54 W	80	11.90
	111-1096	LED-12/6W/6W / 350 mA - 2700 K	1511.9	14 W	80	11.60
	111-1097	LED-12/12W/12W / 700 mA - 2700 K	2681.3	27 W	80	11.60
	111-1098	LED-24/12W/12W / 350 mA - 2700 K	3023.8	27 W	80	11.90

RFS530 LED

Catenary luminaires



Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
	111-1099	LED-24/24W/24W / 700 mA - 2700 K	5362.6	54 W	80	11.90

WE-EF LIGHTING Pty Ltd

6/13 Downard Street, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499

info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 23/11/2024

RFS530 LED

Catenary luminaires

Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim® Advanced LED	430-0002

R2C Ready to Connect

Description	Part ID
R2C Ready to Connect (top)	430-0019