we-ef

Recessed Wall Luminaires



3.62" 9.25 x 2.99" 9.84" 0.71" 3.94"

Description

Floor-grazing steplight, designed for wide pathways.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming standard.

A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



Recessed Wall Luminaires

Specifications Material description

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Prismatic polycarbonate lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

IP55 Ingress protection IK10 Impact resistance Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Additional information

Listings

Lifetime $Ta=25^{\circ}/40^{\circ} L80B10 > 54000h$ ETL Listed. Suitable for wet locations.

WE-EF LIGHTING USA, LLC

we-ef

Recessed Wall Luminaires

Options

Light distribution Color temperature Nominal Watt



Recessed Wall Luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (lb)
			lumens	power		



Recessed Wall Luminaires

Mounting Accessories

Installation blockout

Description	Part ID	Α	В	C1	С
Installation blockout BST25-I	133-0076	10.51"	5.19"	5.12"	130

