

## **Description**

IP55, Class I. Class II on request. IK10. Marine-grade, diecast aluminium alloy, with polished stainless steel frame. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter.

A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

Optional 2200 K version available. To be specified at time of ordering.

## STG259 LED Stainless steel



#### Wall luminaires recessed

# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Polycarbonate lens

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

## **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

Surge protection 1/2 kV

#### Additional information

Lifetime  $Ta=25^{\circ} L80B10 > 54000h$ 

Energy efficiency class C-D (Light source)


## Wall luminaires recessed

# **Options Light distribution**

+ diffused distribution

## **Colour temperature Nominal Watt**

1 W



## **STG259 LED Stainless steel**



## Wall luminaires recessed

## **Configurations**


Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
diffused distribution	133-0345	LED-6/6W / 350 mA - 3000 K	94.9	7.5 W	80	1.80
	133-0346	LED-6/6W / 350 mA - 4000 K	104.1	7.5 W	80	1.90
	133-0452	LED-6/6W / 350 mA - 2700 K	88.8	7.5 W	80	1.80
	133 0432	ELD 0/0W/ 330 IIIA 2700 K	00.0	7.5 W	00	1.00

## Wall luminaires recessed

## **Mounting Accessories**

## **Installation blockout**

Description	Part ID	Α	В	C1	С
Installation blockout BST25-I	133-0076	267	132	130	130



Installation blockout BST25-II 133-0078 267 132 140 140

