



### **Description**

Recessed LED wall luminaire.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. 0-10V Dimming comes standard with luminaire.

A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



# **Specifications**

## **Material description**

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Tempered glass lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP55
Impact resistance IK08
Corrosion resistance 5CE

### **Electrical description**

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral FC electronic converter

### **Additional information**

Lifetime	LED >60,000 h Ta 25°(B10/70) Control gear >50,000 h Ta 25°
Listings	ETL listed. Suitable for wet locations.



# Options Light distribution



asymmetric, forward-throw [A60]

asymmetric, forward throw [A60]

## **Color temperature Nominal Watt**

1 W

0 W

3000 K

4000 K

2700 K



# **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
asymmetric, forward throw [A60]	197-9084	LED-12W / 350 mA - 3000 K	511.9	15 W	80	3.40
	197-9086	LED-12W / 350 mA - 4000 K	531	15 W	80	3.40
	197-9090	LED-6W / 350 mA - 2700 K	376.9	8 W	80	7.10
	197-9091	LED-12W / 350 mA - 2700 K	473.6	15 W	80	7.10
asymmetric, forward-throw [A60]	197-0352	LED-6/6W / 350 mA - 3000 K	354	7.7 W	80	7.10
	197-0353	LED-6/6W / 350 mA - 4000 K	388.3	5.6 W	80	7.10



# **Mounting Accessories**

## **Installation blockout**

Description	Part ID	А	В	C1	C
Installation blockout BQR35-I-RE	197-0129	10.70	10.70	4.92	125

