

#### **Description**

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. Two cable entries. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation in non-insulated ceiling. A preinstallation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

### **DOC220 LED Stainless Steel**



#### **Ceiling Luminaires**

# Specifications Material description

Body Luminaire body constructed in die cast aluminum.

Lens Clear tempered glass lens.

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

## **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

#### **Additional information**

Lifetime	LED >60,000 h Ta 25°(L70/B10) Control gear >50.000 h Ta 25°
Listings	ETL listed. Suitable for wet applications.



# Options Light distribution



symmetric, very narrow beam, 'sharp cut-off' [VNS]



symmetric, very narrow beam [VN]



symmetric, medium beam [M]



symmetric, wide beam [W]



linear spread, medium beam [M]

## **Color temperature Nominal Watt**



4000 K



# **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
linear spread, medium beam [M]	134-6115+134-1381	LED-12/24W / 700 mA - 3000 K	2944.8	27 W	80	6.40
	134-6125+134-1381	LED-12/24W / 700 mA - 4000 K	3147.9	27 W	80	6.40
symmetric, medium beam [M]	134-6115	LED-12/24W / 700 mA - 3000 K	2998.6	27 W	80	6.40
	134-6125+134-1381	LED-12/24W / 700 mA - 4000 K	3205.4	27 W	80	6.40
symmetric, very narrow beam [VN]	134-6116	LED-12/24W / 700 mA - 3000 K	2883.7	27 W	80	6.40
	134-6126	LED-12/24W / 700 mA - 4000 K	3082.5	27 W	80	6.40
symmetric, very narrow beam, 'sharp	134-6117+134-1381	LED-12/24W / 700 mA - 3000 K	3077.9	27 W	80	6.40
cut-off' [VNS]	134-6123	LED-12/24W / 700 mA - 4000 K	3290.2	27 W	80	6.40
symmetric, wide beam [W]	134-6118+134-1440	LED-12/24W / 700 mA - 3000 K	2709.2	27 W	80	6.40
	134-6124+134-1381	LED-12/24W / 700 mA - 4000 K	2896	27 W	80	6.40




# **Mounting Accessories**

## **Installation blockout**

Description	Part ID	Α	В	C1	С			
Installation blockout BDO22-I	134-0797	15.08"	7.87"	8.23"	195			







# **Optical Accessories**

## **Softening Lens**

Description	Part ID	C1
IO-360-DAC/DOC220-LED	134-1440	4.13





## **Honeycomb louvre**

Description	Part ID	C1	
IW-DOC22_LED	134-1444	4.13	



## Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC220-LED	134-1491	4.13



## **DOC220 LED Stainless Steel**



## **Ceiling Luminaires**

## **Linear spread lens**

Description	Part ID	C1
IO-180-DAC/DOC220-LED	134-1381	4.13

