

### Description

Vertically oriented, diffused steplight.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Opal polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming standard.

A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



# **Specifications**

## **Material description**

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Opal polycarbonate lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

### **Electrical description**


Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral FC electronic converter

### **Additional information**

Lifetime	Ta=25°/40° L80B10 > 54000h
Listings	ETL listed. Suitable for wet locations.



# Options Light distribution



## **Color temperature Nominal Watt**

3000 K

4000 K

2700 K

1 W



# **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
diffused distribution	133-0323	LED-6/6W / 350 mA - 3000 K	219.3	7.5 W	80	2.40
	133-0325	LED-6/6W / 350 mA - 4000 K	240.5	7.5 W	80	2.40
	133-0440	LED-6/6W / 350 mA - 2700 K	205.2	7.5 W	80	2.40



# **Mounting Accessories**

### **Installation blockout**

Description	Part ID	Α	В	C1
Installation blockout BST25-I	133-0076	10.51"	5.19"	5.12"

