

## **Description**

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter. Optional 2200 K version available. To be specified at time of ordering.

A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.



# **Specifications Material description**

Body Marine-grade die-cast aluminium alloy

Lens Polycarbonate lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK10

Corrosion resistance 5CE+Primer

## **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

## Additional information

Lifetime  $Ta=40^{\circ} L80B10 > 54000h$ 

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.



# Options

# Light distribution Colour temperature Nominal Watt 15 W 4000 K 2700 K



# **Configurations**


Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
diffused distribution	133-0352	LED-9/21W / 500 mA - 3000 K	802.5	24 W	80	2.30
	133-0353	LED-9/21W / 500 mA - 4000 K	857.4	24 W	80	2.30
+	133-0447	LED-9/21W / 500 mA - 2700 K	747.5	24 W	80	2.30



## **Mounting Accessories**

## **Installation blockout**

Description	Part ID	Α	В	C1	С
Installation blockout BST27-I	133-0217	447	157	125	130



Installation blockout BST27-II 133-0219 447 157 135 140

