**Description**

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter. Optional 2200 K version available. To be specified at time of ordering.

A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

Wall luminaires recessed**Specifications****Material description**

Body	Marine-grade die-cast aluminium alloy
Lens	Polycarbonate lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP66
Impact resistance	IK10
Corrosion resistance	5CE+Primer

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter

Additional information

Lifetime	T _a =40° L80B10 > 54000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Options**Light distribution**

diffused distribution

Colour temperature

3000 K

4000 K

2700 K

Nominal Watt


15 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
diffused distribution	133-0352	LED-9/21W / 500 mA - 3000 K	802.5	24 W	80	2.30
	133-0353	LED-9/21W / 500 mA - 4000 K	857.4	24 W	80	2.30
+	133-0447	LED-9/21W / 500 mA - 2700 K	747.5	24 W	80	2.30

Wall luminaires recessed**Mounting Accessories****Installation breakout**

Description	Part ID	A	B	C1	C
Installation breakout BST27-I	133-0217	447	157	125	130



Installation breakout BST27-II	133-0219	447	157	135	140
--------------------------------	----------	-----	-----	-----	-----

