

Description

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. Two cable entries. PMMA-Diffusor-Lens for glare control and soft wide beam distribution. Anodized aluminum reflector. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation in non-insulated ceiling. A preinstallation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



Specifications

Material description

Body Luminaire body constructed in die cast aluminum.

Lens Clear tempered glass lens.

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Additional information

Lifetime LED >60,000 h Ta 25° (L70/B10)

Control gear >50.000 h Ta 25°


Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



Options Light distribution



symmetric, wide beam, Darklight [BD]



DOC220-FT LED Stainless Steel



Ceiling Luminaires

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
symmetric, wide beam, Darklight	134-6149	LED-FT-24W (3000K)	2266.6	27 W	80	7.10
[BD]	134-6150	LED-FT-24W (4000K)	2364.6	27 W	80	7.10





Mounting Accessories

Installation blockout

Description	Part ID	А	В	C1	С			
Installation blockout BDO22-I	134-0797	15.08"	7.87"	8.23"	195			



