
we-ef


Inground luminaires



we-ef

Inground luminaires





Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

'No tool' removable gear/reflector tray. Gimbal mounted, 360° rotable and 30° tilt. Factory installed circuit board with High Efficiency LEDs. PMMA LED Lens array.

Luminaire requires installation blockout and sealable junction box, which are included in supply.



Inground luminaires

Specifications

Material description

Body Stainless steel construction

Lens Safety glass lens; max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP67
Impact resistance IK10+
Corrosion resistance 5CE

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Lifetime Ta=40° L90B10 > 90000h

we-ef

Inground luminaires

Options

Light distribution Colour temperature Nominal Watt



Inground luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		



Inground luminaires

Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300



WE-EF LIGHTING Pty Ltd




Inground luminaires

Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19





Inground luminaires

Optical Accessories

Linear spread lens

Description	Part ID	C1
IO-180-6 ETC140-GB-LED	185-2719	149



Linear spread lens IO-180 185-7170 191

