

### Description

IP55, Class I. IK07. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket.





Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries.

Knuckle permits 350° horizontal and 180° vertical aiming of optics.

### Specifications

#### Material description

---

Body	Marine-grade, all-aluminium construction
Lens	Safety glass lens
Colours	 RAL9004 Signal black  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS hardware
Ingress protection	IP55
Impact resistance	IK07
Corrosion resistance	5CE

---

#### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

---

#### Additional information

---

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

---

# FLC141 LED Wall bracket

## Projectors

### Options

#### Light distribution



symmetric, medium beam [M]



symmetric, very narrow beam, sharp cut-off [EES]



symmetric, wide beam [B]



symmetric, very narrow beam [EE]



linear spread, very narrow beam [EE]



linear spread, very narrow beam, sharp cut-off [EES]



wallwash

#### Colour temperature



3000 K



4000 K










2700 K

#### Nominal Watt

56 W

### Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
linear spread, very narrow beam [EE] 	146-0978+146-0439	LED-24/48W / 700 mA - 2700 K	5162.8	54 W	80	5.80
	146-7068+146-0439	LED-24/48W / 700 mA - 3000 K	5545.2	54 W	80	5.80
	146-7069+146-0439	LED-24/48W / 700 mA - 4000 K	5927.6	54 W	80	5.80
linear spread, very narrow beam, sharp cut-off [EES] 	146-0979+146-0439	LED-24/48W / 700 mA - 2700 K	5683.9	54 W	80	5.80
	146-7056+146-0439	LED-24/48W / 700 mA - 3000 K	6104.9	54 W	80	5.80
	146-7057+146-0439	LED-24/48W / 700 mA - 4000 K	6526	54 W	80	5.80
symmetric, medium beam [M] 	146-0977	LED-24/48W / 700 mA - 2700 K	5630.1	54 W	80	5.80
	146-7054	LED-24/48W / 700 mA - 3000 K	6047.2	54 W	80	5.80
	146-7055	LED-24/48W / 700 mA - 4000 K	6464.2	54 W	80	5.80
symmetric, very narrow beam [EE] 	146-0978	LED-24/48W / 700 mA - 2700 K	5573.3	54 W	80	5.80
	146-7068	LED-24/48W / 700 mA - 3000 K	5986.1	54 W	80	5.80
	146-7069	LED-24/48W / 700 mA - 4000 K	6398.9	54 W	80	5.80
symmetric, very narrow beam, sharp cut-off [EES] 	146-0979	LED-24/48W / 700 mA - 2700 K	5998.4	54 W	80	5.80
	146-7056	LED-24/48W / 700 mA - 3000 K	6442.7	54 W	80	5.80
	146-7057	LED-24/48W / 700 mA - 4000 K	6887	54 W	80	5.80
symmetric, wide beam [B] 	146-0976	LED-24/48W / 700 mA - 2700 K	5016.9	54 W	80	5.80
	146-7066	LED-24/48W / 700 mA - 3000 K	5388.5	54 W	80	5.80
	146-7067	LED-24/48W / 700 mA - 4000 K	5760.1	54 W	80	5.80
wallwash 	146-0977+146-0646	LED-24/48W / 700 mA - 2700 K	4517.3	54 W	80	5.80
	146-7054+146-0646	LED-24/48W / 700 mA - 3000 K	4851.9	54 W	80	5.80
	146-7055+146-0646	LED-24/48W / 700 mA - 4000 K	5186.6	54 W	80	5.80

### Optical Accessories


#### Glare shield

Description	Part ID	A	C1
Glare shield ES	146-0229	120	145



#### Snoot

Description	Part ID	A	C1
Snoot ET	146-0398	120	145



## Projectors


### Linear louvre

Description	Part ID	C1
Linear louvre IL	146-9056	145



### Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	146-0626	145



## Projectors

### Colour correction filter

Description	Part ID
IF-3000K > 2400K	146-9058

