



Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens with opal diffuser, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Complete with cable gland and 0.5 m of flexible PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. Luminaire installation blockout and sealable junction box included in supply.

2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.



Specifications Material description

Body Stainless steel construction

Lens Safety glass lens with opal diffuser, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details. Warranty void if installed without proper

drainage.



Options Light distribution



symmetric, diffused distribution

Colour temperature Nominal Watt

9 W



3000 K

4000 K



Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, diffused distribution	185-7251	LED-3/6W / 700 mA - 3000 K	197	7.5 W	80	3.80
	185-7252	LED-3/6W / 700 mA - 4000 K	210.6	7.5 W	80	3.80



Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0796	160


