



Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 0,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

Integral EC electronic converter.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

we-ef

Inground luminaires

Specifications Material description

Body Stainless steel construction

Lens Safety glass lens with opal diffuser, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details. Warranty void if installed without proper

drainage.



Options Light distribution



symmetric, diffused distribution

Colour temperature Nominal Watt

3000 K

17 W

4000 K



Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, diffused distribution	185-7261	LED-6/12W / 700 mA - 3000 K	369.2	14.5 W	80	6.30
	185-7262	LED-6/12W / 700 mA - 4000 K	394.7	14.5 W	80	6.30



Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250

