

---

**Description**

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens with opal diffuser, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Complete with cable gland and 0.5 m of flexible PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

|                    |                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------|
| Body               | Stainless steel construction                                                                      |
| Lens               | Safety glass lens with opal diffuser, max. load 5 tonnes                                          |
| Colours            |  Stainless Steel |
| Gasket             | Silicone rubber gasket                                                                            |
| Fasteners          | PCS hardware                                                                                      |
| Ingress protection | IP69                                                                                              |
| Impact resistance  | IK10+                                                                                             |

Electrical description

|                  |                                  |
|------------------|----------------------------------|
| Driver / Ballast | Integral EC electronic converter |
|------------------|----------------------------------|

Additional information

Options

Light distribution



symmetric, diffused distribution

Colour temperature



3000 K




4000 K

Nominal Watt

9 W

Configurations

| Light distribution               | Part ID  | Light source               | Rated lumens | Rated input power | CRI | Weight (kg) |
|----------------------------------|----------|----------------------------|--------------|-------------------|-----|-------------|
| symmetric, diffused distribution | 185-7254 | LED-3/6W / 700 mA - 3000 K | 197          | 7.5 W             | 80  | 4.20        |
|                                  | 185-7255 | LED-3/6W / 700 mA - 4000 K | 210.6        | 7.5 W             | 80  | 4.20        |



**Control****DALI interface**

| Description    | Part ID  |
|----------------|----------|
| DALI interface | 430-0013 |

**1-10 V analogue dimming interface**

| Description                       | Part ID  |
|-----------------------------------|----------|
| 1-10 V analogue dimming interface | 430-0011 |

Mounting Accessories

Installation cover

| Description           | Part ID  | C1  |
|-----------------------|----------|-----|
| Installation cover BE | 185-0796 | 160 |

