
we-ef

Inground luminaires





Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 0.5 m of flexible PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD- optimised optics for superior illumination and glare control; 20° tiltable and 355° rotatable.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

ASC Anti Slip Coating on request.



Inground luminaires

Specifications Material description

Colours

Stainless Steel

Electrical description

Additional information



Inground luminaires

Options

Light distribution Colour temperature Nominal Watt



Inground luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		



Inground luminaires

Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0796	160



Fagerhult Lighting Ltd




Inground luminaires

Optical Accessories

Honeycomb louvre

Description	Part ID	C1	
Honeycomb Louvre	185-2869	60	



Linear spread lens

Description	Part ID	C1
Linear spread ler	180 185-9612	60



Fagerhult Lighting Ltd



Inground luminaires

Fagerhult Lighting Ltd

33-34 Dolben Street, SE1 0UQ London, United Kingdom

https://we-ef.com/uk

Subject to technical changes and errors. Generated on 23/10/2024

