

## ETC320-GB LED


### Inground Luminaires

**we-ef**



#### Description

IP67. Inground uplight. Suitable for flush installation in concrete or earth. Special effects and distributions can be realized with linear lens, flood lens, 6° directional lens, 20° directional lens, or color filters.



#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 06/08/2025

# ETC320-GB LED



Inground Luminaires

## Specifications

### Material description









Colors	 Stainless Steel
--------	---

### Electrical description


### Additional information

Options

Light distribution

- symmetric, very narrow beam [VN]
- symmetric, medium beam [M]
- symmetric, very narrow beam, 'sharp cut-off' [VNS]
- flood, medium beam [M]
- symmetric, narrow beam [N]
- symmetric, narrow beam, 'sharp cut-off'
- linear spread, very narrow beam [VN]
- linear spread, very narrow beam, 'sharp cut-off'

Color temperature









2700 K

Nominal Watt

0 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
flood, medium beam [M] 	185-9792+185-9613	LED-3/6W / 700 mA - 2700 K	597.9	7.5 W	80	10.10
linear spread, very narrow beam [VN] 	185-9793+185-9612	LED-3/6W / 700 mA - 2700 K	586.6	7.5 W	80	10.10
linear spread, very narrow beam, 'sharp cut-off' 	185-9794+185-9612	LED-3/6W / 700 mA - 2700 K	615.7	7.5 W	80	10.10
symmetric, medium beam [M] 	185-9792	LED-3/6W / 700 mA - 2700 K	593.2	7.5 W	80	10.10
	185-9792+185-9612	LED-3/6W / 700 mA - 2700 K	623.6	7.5 W	80	10.10
symmetric, narrow beam [N] 	185-9793+185-9613	LED-3/6W / 700 mA - 2700 K	563.6	7.5 W	80	10.10
symmetric, narrow beam, 'sharp cut-off' 	185-9794+185-9613	LED-3/6W / 700 mA - 2700 K	611	7.5 W	80	10.10
symmetric, very narrow beam [VN]	185-7788	LED-3/9W / 1050 mA - 2700 K	1009.5	11 W	80	10.00
	185-9793	LED-3/6W / 700 mA - 2700 K	605.8	7.5 W	80	10.10

## WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030



customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 06/08/2025

ETC320-GB LED

Inground Luminaires




Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
						
symmetric, very narrow beam, 'sharp cut-off' [VNS]	185-9794	LED-3/6W / 700 mA - 2700 K	652.3	7.5 W	80	10.10
						

Optical Accessories

Honeycomb louvre

Description	Part ID	C1
IW-ETC120_GB_LED Honeycomb louvre	185-2869	2.89



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-9612	2.36

