


# ETC320-GB LED

## Inground Luminaires

**we-ef**



### Description

IP67. Inground upright. Suitable for flush installation in concrete or earth. Special effects and distributions can be realized with linear lens, flood lens, 6° directional lens, 20° directional lens, or color filters.

#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

# ETC320-GB LED

## Inground Luminaires



### Specifications

#### Material description

---

Colors



Stainless Steel

---

#### Electrical description

#### Additional information

#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

# ETC320-GB LED

## Inground Luminaires

### Options

#### Light distribution



symmetric, very narrow beam [VN]



symmetric, medium beam [M]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



flood, medium beam [M]



symmetric, narrow beam [N]



symmetric, narrow beam, 'sharp cut-off'



linear spread, very narrow beam [VN]



linear spread, very narrow beam, 'sharp cut-off'

#### Color temperature



2700 K

#### Nominal Watt








0 W

#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (lb)
flood, medium beam [M] 	185-9792+185-9613	LED-3/6W / 700 mA - 2700 K	597.9	7.5 W	80	10.10
linear spread, very narrow beam [VN] 	185-9793+185-9612	LED-3/6W / 700 mA - 2700 K	586.6	7.5 W	80	10.10
linear spread, very narrow beam, 'sharp cut-off' 	185-9794+185-9612	LED-3/6W / 700 mA - 2700 K	615.7	7.5 W	80	10.10
symmetric, medium beam [M] 	185-9792	LED-3/6W / 700 mA - 2700 K	593.2	7.5 W	80	10.10
	185-9792+185-9612	LED-3/6W / 700 mA - 2700 K	623.6	7.5 W	80	10.10
symmetric, narrow beam [N] 	185-9793+185-9613	LED-3/6W / 700 mA - 2700 K	563.6	7.5 W	80	10.10
symmetric, narrow beam, 'sharp cut-off' 	185-9794+185-9613	LED-3/6W / 700 mA - 2700 K	611	7.5 W	80	10.10
symmetric, very narrow beam [VN] 	185-7788	LED-3/9W / 1050 mA - 2700 K	1009.5	11 W	80	10.00
	185-9793	LED-3/6W / 700 mA - 2700 K	605.8	7.5 W	80	10.10

## WE-EF LIGHTING USA, LLC



410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

# ETC320-GB LED

## Inground Luminaires

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (lb)
						
symmetric, very narrow beam, 'sharp cut-off' [VNS]	185-9794	LED-3/6W / 700 mA - 2700 K	652.3	7.5 W	80	10.10
						

### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>  
Subject to technical changes and errors. - Generated on 11/23/2024


**Optical Accessories**

**Honeycomb louvre**

---

Description	Part ID	C1
IW-ETC120_GB_LED Honeycomb louvre	185-2869	2.89

---



**Linear spread lens**

---

Description	Part ID	C1
Linear spread lens IO-180	185-9612	2.36

---

