**Description**

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blackout and sealable junction box included in supply.

Specifications**Material description**

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

Electrical description

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Options

Light distribution



symmetric, medium beam [M]



symmetric, very narrow beam [EE]



symmetric, very narrow beam, sharp cut-off [EES]



linear spread, very narrow beam [EE]



linear spread, very narrow beam, sharp cut-off [EES]



flood, medium beam [M]



flood, very narrow beam [EE]



flood, narrow beam, sharp cut-off [EES]

Colour temperature



3000 K



4000 K









2700 K

Nominal Watt



8 W

0 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
flood, medium beam [M] 	185-7023+185-9613	LED-3/6W / 700 mA - 3000 K	642.2	7.5 W	80	4.00
	185-7026+185-9613	LED-3/6W / 700 mA - 4000 K	686.5	7.5 W	80	4.00
	185-9792+185-9613	LED-3/6W / 700 mA - 2700 K	597.9	7.5 W	80	4.00
flood, narrow beam, sharp cut-off [EES] 	185-7710+185-9613	LED-3/6W / 700 mA - 3000 K	656.3	7.5 W	80	4.00
	185-7712+185-9613	LED-3/6W / 700 mA - 4000 K	701.5	7.5 W	80	4.00
	185-9794+185-9613	LED-3/6W / 700 mA - 2700 K	611	7.5 W	80	4.00
flood, very narrow beam [EE] 	185-7024+185-9613	LED-3/6W / 700 mA - 3000 K	605.3	7.5 W	80	4.00
	185-7027+185-9613	LED-3/6W / 700 mA - 4000 K	647.1	7.5 W	80	4.00
	185-9793+185-9613	LED-3/6W / 700 mA - 2700 K	563.6	7.5 W	80	4.00
linear spread, very narrow beam [EE] 	185-7024+185-9612	LED-3/6W / 700 mA - 3000 K	630	7.5 W	80	4.00
	185-7027+185-9612	LED-3/6W / 700 mA - 4000 K	673.5	7.5 W	80	4.00
	185-9793+185-9612	LED-3/6W / 700 mA - 2700 K	586.6	7.5 W	80	4.00
linear spread, very narrow beam, sharp cut-off [EES] 	185-7710+185-9612	LED-3/6W / 700 mA - 3000 K	661.3	7.5 W	80	4.00
	185-7712+185-9612	LED-3/6W / 700 mA - 4000 K	706.9	7.5 W	80	4.00
	185-9794+185-9612	LED-3/6W / 700 mA - 2700 K	615.7	7.5 W	80	4.00
symmetric, medium beam [M] 	185-7023	LED-3/6W / 700 mA - 3000 K	637.2	7.5 W	80	4.00
	185-7023+185-9612	LED-3/6W / 700 mA - 3000 K	669.8	7.5 W	80	4.00
	185-7026	LED-3/6W / 700 mA - 4000 K	681.1	7.5 W	80	4.00
	185-7026+185-9612	LED-3/6W / 700 mA - 4000 K	716	7.5 W	80	4.00
	185-7744	LED-3/9W / 1050mA - 3000 K	965.4	11 W	80	4.00
	185-7748	LED-3/9W / 1050mA - 4000 K	1010.3	11 W	80	4.00
	185-7787	LED-3/9W / 1050 mA - 2700 K	920.5	11 W	80	4.00
	185-9792	LED-3/6W / 700 mA - 2700 K	593.2	7.5 W	80	4.00
	185-9792+185-9612	LED-3/6W / 700 mA - 2700 K	623.6	7.5 W	80	4.00
	185-7024	LED-3/6W / 700 mA - 3000 K	650.7	7.5 W	80	4.00

Inground luminaires

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
	185-7027	LED-3/6W / 700 mA - 4000 K	695.6	7.5 W	80	4.00
	185-7745	LED-3/9W / 1050mA - 3000 K	960.3	12 W	80	4.00
	185-7749	LED-3/9W / 1050mA - 4000 K	1108	12 W	80	4.00
	185-7788	LED-3/9W / 1050 mA - 2700 K	1009.5	11 W	80	4.00
	185-9793	LED-3/6W / 700 mA - 2700 K	605.8	7.5 W	80	4.00
symmetric, very narrow beam, sharp cut-off [EES] 	185-7710	LED-3/6W / 700 mA - 3000 K	700.7	7.5 W	80	4.00
	185-7712	LED-3/6W / 700 mA - 4000 K	749	7.5 W	80	4.00
	185-9794	LED-3/6W / 700 mA - 2700 K	652.3	7.5 W	80	4.00

Control**DALI interface**

Description	Part ID
DALI interface	430-0013


1-10 V analogue dimming interface

Description	Part ID
1-10 V analogue dimming interface	430-0011

Mounting Accessories

Installation cover


Description	Part ID	C1
Installation cover BE	185-0796	160



Optical Accessories


Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	185-2869	60



Linear spread lens


Description	Part ID	C1
Linear spread lens IO-180	185-9612	60



Inground luminaires

Flood lens

Description	Part ID	C1
Flood lens IO-360	185-9613	60



Linear louvre


Description	Part ID	Additional information	C1
Linear louvre IL	185-9614	ETC320	60



Inground luminaires

Colour filter

Description	Part ID
Colour filter IF	on request



Colour correction filter

Description	Part ID
IF-3000K > 2400K	185-9973

