

Description

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

Electrical description

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Options

Light distribution

Colour temperature

Nominal Watt



symmetric, wide beam [B]




3000 K

42 W

0 W



symmetric, very narrow beam, sharp cut-off [EES]



4000 K



symmetric, very narrow beam [EE]



2700 K



symmetric, medium beam [M]



wallwash



linear spread, very narrow beam [EE]



flood, very narrow beam [EE]



linear spread, very narrow beam, sharp cut-off [EES]







flood, narrow beam, sharp cut-off [EES]




symmetric, wallgrazer [A6]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
flood, narrow beam, sharp cut-off [EES] 	185-7698+185-7579	LED-24/36W / 500 mA - 3000 K	4479.9	39 W	80	11.00
	185-7700+185-7579	LED-24/36W / 500 mA - 4000 K	4792.5	39 W	80	11.00
flood, very narrow beam [EE] 	185-9748+185-7579	LED-24/36W / 500 mA - 3000 K	4111.2	39 W	80	11.00
	185-9752+185-7579	LED-24/36W / 500 mA - 4000 K	4398	39 W	80	11.00
linear spread, very narrow beam [EE] 	185-9748+185-7580	LED-24/36W / 500 mA - 3000 K	4028.9	39 W	80	11.00
	185-9752+185-7580	LED-24/36W / 500 mA - 4000 K	4310	39 W	80	11.00
linear spread, very narrow beam, sharp cut-off [EES] 	185-7698+185-7580	LED-24/36W / 500 mA - 3000 K	4435.8	39 W	80	11.00
	185-7700+185-7580	LED-24/36W / 500 mA - 4000 K	4745.3	39 W	80	11.00
symmetric, medium beam [M] 	185-9749	LED-24/36W / 500 mA - 3000 K	4542.4	39 W	80	11.00
	185-9753	LED-24/36W / 500 mA - 4000 K	4859.4	39 W	80	11.00
symmetric, very narrow beam [EE] 	185-9748	LED-24/36W / 500 mA - 3000 K	4439.5	39 W	80	11.00
	185-9752	LED-24/36W / 500 mA - 4000 K	4749.2	39 W	80	11.00
symmetric, very narrow beam, sharp cut-off [EES] 	185-7698	LED-24/36W / 500 mA - 3000 K	4818.2	39 W	80	11.00
	185-7700	LED-24/36W / 500 mA - 4000 K	5154.3	39 W	80	11.00

Inground luminaires

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, wallgrazer [A6] 	185-7886	LED-24/36W / 500 mA - 3000 K	3875.1	39 W	80	11.00
	185-7887	LED-24/36W / 500 mA - 4000 K	4145.5	39 W	80	11.00
	185-7888	LED-24/36W / 500 mA - 2700K	3604.8	39 W	80	11.00
symmetric, wide beam [B] 	185-7697	LED-24/36W / 500 mA - 3000 K	4043.5	39 W	80	11.00
	185-7699	LED-24/36W / 500 mA - 4000 K	4325.6	39 W	80	11.00
wallwash 	185-9749+185-7589	LED-24/36W / 500 mA - 3000 K	3497.6	39 W	80	11.00
	185-9753+185-7589	LED-24/36W / 500 mA - 4000 K	3741.7	39 W	80	11.00

Control**DALI interface**

Description	Part ID
DALI interface	430-0013


1-10 V analogue dimming interface

Description	Part ID
1-10 V analogue dimming interface	430-0011

Mounting Accessories

Installation cover


Description	Part ID	C1
Installation cover BE	185-0326	300



Optical Accessories


Flood lens

Description	Part ID	C1
Flood lens IO-360	185-7579	220



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220



Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220

