

Description

IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description


Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

Electrical description




Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Options

Light distribution		Colour temperature	Nominal Watt
	symmetric, wide beam [B]	 3000 K	42 W 0 W
	symmetric, very narrow beam, sharp cut-off [EES]	 4000 K	
	symmetric, very narrow beam [EE]	 2700 K	
	symmetric, medium beam [M]		
	wallwash		
	symmetric, wallgrazer [A6]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-9764	LED-24/36W / 500 mA - 3000 K	4542.4	39 W	80	12.00
	185-9768	LED-24/36W / 500 mA - 4000 K	4859.4	39 W	80	12.00
symmetric, very narrow beam [EE] 	185-9763	LED-24/36W / 500 mA - 3000 K	4439.5	39 W	80	12.00
	185-9767	LED-24/36W / 500 mA - 4000 K	4749.2	39 W	80	12.00
symmetric, very narrow beam, sharp cut-off [EES] 	185-7706	LED-24/36W / 500 mA - 3000 K	4818.2	39 W	80	12.00
	185-7708	LED-24/36W / 500 mA - 4000 K	5154.3	39 W	80	12.00
symmetric, wallgrazer [A6] 	185-7898	LED-24/36W / 500 mA - 3000 K	3875.1	39 W	80	12.00
	185-7899	LED-24/36W / 500 mA - 4000 K	4145.5	39 W	80	12.00
	185-7900	LED-24/36W / 500 mA - 2700K	3604.8	39 W	80	12.00
symmetric, wide beam [B] 	185-7705	LED-24/36W / 500 mA - 3000 K	4043.5	39 W	80	12.00
	185-7707	LED-24/36W / 500 mA - 4000 K	4325.6	39 W	80	12.00
wallwash 	185-9764+185-7589	LED-24/36W / 500 mA - 3000 K	3497.6	39 W	80	12.00
	185-9768+185-7589	LED-24/36W / 500 mA - 4000 K	3741.7	39 W	80	12.00

Control**DALI interface**

Description	Part ID
DALI interface	430-0013


1-10 V analogue dimming interface

Description	Part ID
1-10 V analogue dimming interface	430-0011

Mounting Accessories

Installation cover


Description	Part ID	C1
Installation cover BE	185-0326	300



Optical Accessories


Flood lens

Description	Part ID	C1
Flood lens IO-360	185-7579	220



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220



Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220

