
# we-ef

#### **Surface Mounted Wall Luminaires**





#### **Description**

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket.

Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

#### XLO229 LED



#### **Surface Mounted Wall Luminaires**

# Specifications Material description

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Opal polycarbonate lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

# **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

## **Additional information**

Lifetime Ta=25°/40° L70B50 > 50000h

Listings Contact WE-EF USA for ETL/UL certification status. compliant.

## **XLO229 LED**

we-ef

**Surface Mounted Wall Luminaires** 

**Options** 

Light distribution Color temperature Nominal Watt

## **XLO229 LED**



## **Surface Mounted Wall Luminaires**

# **Configurations**

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (lb)
			lumens	power		