





Description

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone rubber gasket. Two cable entries.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output.



Wall luminaires surface mounted

Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK10

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Lifetime $Ta=40^{\circ} L70B50 > 50000h$

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.

Wall luminaires surface mounted

Options

Light distribution Colour temperature Nominal Watt 15 W 3000 K diffused distribution 4000 K

2700 K

DLO229 LED



Wall luminaires surface mounted

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI | Weight (kg) |
|-----------------------|----------|------------------------------|-----------------|----------------------|-----|-------------|
| diffused distribution | 195-0893 | LED-FT-17W / 500 mA - 2700 K | 1346.8 | 20 W | 80 | 2.00 |
| | 195-9521 | LED-FT-17W / 500 mA - 3000 K | 1408.7 | 20 W | 80 | 2.00 |
| + | 195-9522 | LED-FT-17W / 500 mA - 4000 K | 1468.4 | 20 W | 80 | 2.00 |
| | | | | | | |