






Description

IP66, Class I, IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG[®] Controlled Compression Gasket. Safety glass lens. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during the installation. Optional 2200 K version available. To be specified at time of ordering.

Specifications**Material description**

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV

Additional information

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	C-D (Light source)

FLD131 LED

Projectors

we-ef

Options

Light distribution



symmetric, medium beam [M]



symmetric, very narrow beam [EE]



symmetric, wide beam [B]



symmetric, very narrow beam, sharp cut-off [EES]



wallwash

Colour temperature



3000 K



4000 K








2700 K

Nominal Watt

3 W


Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	145-0317	LED-12/24W / 700 mA - 2700 K	2715.8	27 W	80	2.70
	145-9549	LED-12/24W / 700 mA - 3000 K	2908.1	27 W	80	2.70
	145-9552	LED-12/24W / 700 mA - 4000 K	3108.7	27 W	80	2.70
symmetric, very narrow beam [EE] 	145-0318	LED-12/24W / 700 mA - 2700 K	2570.2	27 W	80	2.70
	145-9550	LED-12/24W / 700 mA - 3000 K	2786.9	27 W	80	2.70
	145-9553	LED-12/24W / 700 mA - 4000 K	2979.1	27 W	80	2.70
symmetric, very narrow beam, sharp cut-off [EES] 	145-0319	LED-12/24W / 700 mA - 2700 K	2779.9	27 W	80	2.70
	145-9605	LED-12/24W / 700 mA - 3000 K	2985.8	27 W	80	2.70
	145-9607	LED-12/24W / 700 mA - 4000 K	3191.8	27 W	80	2.70
symmetric, wide beam [B] 	145-0316	LED-12/24W / 700 mA - 2700 K	2138.3	27 W	80	2.70
	145-9604	LED-12/24W / 700 mA - 3000 K	2296.7	27 W	80	2.70
	145-9606	LED-12/24W / 700 mA - 4000 K	2455	27 W	80	2.70
wallwash 	145-0239	LED-12/24W / 700 mA - 3000 K	2284.9	27 W	80	2.70
	145-0240	LED-12/24W / 700 mA - 4000 K	2442.4	27 W	80	2.70

Mounting Accessories


Ground spike EF

Description	Part ID	H1	Weight (kg)
Ground spike EF1-2/M5 for FLD100	145-9196	270	1.00



Short post EM


Description	Part ID	D1	D2	H1	M1	Weight (kg)
Short post EM1-2/M5	145-9200	160	130	200	9	1.10



Optical Accessories


Glare shield

Description	Part ID	A	C1
Glare shield ES	145-9571	70	134




Snoot

Description	Part ID	A	C1
Snoot ET	145-9572	70	134



Linear spread lens

Description	Part ID	C1
IO-180-FLD131-LED	145-9575	125



Flood lens

Description	Part ID	C1
IO-360-FLD131-LED	145-9576	125

