

Description

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter. Optional 2200 K version available. To be specified at time of ordering.

A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

Wall luminaires recessed

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Polycarbonate lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP55
Impact resistance	IK10
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV

Additional information

Lifetime	Ta=25° L80B10 > 54000h
Energy efficiency class	C-D (Light source)

Options

Light distribution




asymmetric, forward-throw [A60]

Colour temperature



3000 K



4000 K



2700 K

Nominal Watt

7 W

Wall luminaires recessed

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric, forward-throw [A60] 	133-0338	LED-4/4W / 350 mA - 3000 K	141	5.5 W	80	0.90
	133-0339	LED-4/4W / 350 mA - 4000 K	154.6	5.5 W	80	0.90
	133-0455	LED-4/4W / 350 mA - 2700 K	131.9	5.5 W	80	0.90

Mounting Accessories**Installation blackout**

Description	Part ID	A	B	C1	C
Installation blackout BST20-I	133-0075	222	109	105	105

