

Description

IP55. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Surface Mounted Wall Luminaires

Specifications**Material description**

Body	Luminaire body and lens frame constructed in die-cast aluminum.
Lens	Clear tempered glass lens.
Colors	 RAL9004 Black  RAL9007 Grey Metallic  RAL9016 White  RAL8019 Dark Bronze
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP55
Impact resistance	IK07
Corrosion resistance	5CE

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral driver in thermally separated compartment.

Additional information

Ambient Temperature	Ta less than 25 deg C.
Listings	ETL listed. Suitable for wet locations.

Options

Light distribution



symmetric, medium beam [M]



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



symmetric, wide beam [W]

Color temperature



3000 K






4000 K

Nominal Watt

16 W

Surface Mounted Wall Luminaires


Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
symmetric, medium beam [M] 	145-9374	LED-6/12W / 700 mA - 3000 K	1511.8	14.5 W	80	3.50
	145-9377	LED-6/12W / 700 mA - 4000 K	1616.1	14.5 W	80	3.50
symmetric, very narrow beam [VN] 	145-9375	LED-6/12W / 700 mA - 3000 K	1496.5	14.5 W	80	3.50
	145-9378	LED-6/12W / 700 mA - 4000 K	1599.7	14.5 W	80	3.50
symmetric, very narrow beam, 'sharp cut-off' [VNS] 	145-9382	LED-6/12W / 700 mA - 3000 K	1610.7	14.5 W	80	3.50
	145-9384	LED-6/12W / 700 mA - 4000 K	1721.8	14.5 W	80	3.50
symmetric, wide beam [W] 	145-9383	LED-6/12W / 700 mA - 3000 K	1347.1	14.5 W	80	3.50
	145-9385	LED-6/12W / 700 mA - 4000 K	1440	14.5 W	80	3.50

Optical Accessories

Snoot

Description	Part ID	A	C1
Snoot ET	145-0030	2.36"	4.72"



Surface Mounted Wall Luminaires

Glare shield

Description	Part ID	A	C1
Glare shield ES	145-9192	4.02	4.69

