

Description

IP67. 12V - 24V AC/DC. Class III. IK09. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1.5 m of flexible PVC free cable. IP68 in-line connector facilitates easy removal for off-site lamp replacement. Electronic converter required. To be ordered separately. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board.

The optional installation blockout is recommended for mounting. To be ordered separately.

The luminaire is not suitable for permanent underwater operation.

Inground luminaires**Specifications****Material description**

Body	Stainless steel construction
Lens	Safety glass lens; max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP67
Impact resistance	IK09

Electrical description


Driver / Ballast	Electronic converter required. To be ordered separately.
Surge protection	1/2 kV (optional SP10)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	C-D (Light source)

Options

Light distribution





symmetric, medium beam [M]

symmetric, very narrow beam, sharp cut-off [EES]


Colour temperature	Nominal Watt
3000 K	2 W
4000 K	
2700 K	

Configurations


Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-2770	LED-1/2W / 24V AC/DC - 3000 K	233.8	2.5 W	80	1.10
	185-2771	LED-1/2W / 24V AC/DC - 4000 K	249.9	2.5 W	75	1.10
	185-3536	LED-1/2W / 24V AC/DC - 2700 K	217.7	2.5 W	80	1.10
symmetric, very narrow beam, sharp cut-off [EES] 	185-2772	LED-1/2W / 24V AC/DC - 3000 K	226.5	2.5 W	80	1.10
	185-2773	LED-1/2W / 24V AC/DC - 4000 K	242.1	2.5 W	75	1.10
	185-3537	LED-1/2W / 24V AC/DC - 2700 K	210.9	2.5 W	80	1.10

Mounting Accessories**Installation breakout**

Description	Part ID	D1	D2	H1	Weight(kg)	D	H
Breakout, Plastic (shallow)	185-0412	95	240	110	0.50	95/240	110




Breakout, Plastic (deep)	185-0797	95	170	220	0.50	95/170	220
--------------------------	----------	----	-----	-----	------	--------	-----



Installation cover

Description	Part ID	C1
Installation cover BE	185-0414	95




Inground luminaires

Electrical Accessories


Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19




Transformers

Description	Part ID	A	B	C1
Transformer TVM-AC 24 V/20W	185-2884	140	65	90



Inground luminaires

Description	Part ID	A	B	C1
Transformer TVM-AC 24 V/50W	185-2885	140	65	90

**Main converter**

Description	Part ID	A	B	C1
Main converter TVE-DC 24 V/12 W	400-0310	90	61	18

