
we-ef

Inground luminaires





Description

IP67. 12V - 24V AC/DC. Class III. IK09. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. IP68 in-line connector facilitates easy removal for off-site lamp replacement.

Factory installed circuit board with High Efficiency LEDs.



Inground luminaires

Specifications

Material description

Body Stainless steel construcion

Lens Safety glass lens; max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP67
Impact resistance IK09

Electrical description

Driver / Ballast Electronic converter required. To be ordered separately.

Additional information

Lifetime Ta=40° L90B10 > 90000h

we-ef

Inground luminaires

Options

Light distribution Colour temperature Nominal Watt



Inground luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		




Inground luminaires

Electrical Accessories


Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19



Transformers


Description	ion	Part ID	Α	В	C1
Transforme	mer TVM-AC 24 V/20W	185-2884	140	65	90





Inground luminaires

Description	Part ID A	1	В	C1
Transformer TVM-AC 24 V/50W	W 185-2885 1		65	90



Main converter

Description	Part ID	А	В	C1
Main converter TVE-DC 24 V/12 W	400-0310	90	61	18

