

Description

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. Two cable entries. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation in non-insulated ceiling. A preinstallation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

DOC240 LED Stainless Steel



Ceiling Luminaires

Specifications

Material description

Body Luminaire body constructed in die cast aluminum.

Lens Clear tempered glass lens.

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Additional information

Lifetime LED >60,000 h Ta 25° (L70/B10)

Control gear >50.000 h Ta 25°

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



Options Light distribution



symmetric, very narrow beam, 'sharp cut-off' [VNS]



symmetric, very narrow beam [VN]





symmetric, wide beam [W]



wallwash



linear spread, medium beam [M]

Color temperature Nominal Watt

56 W

3000 K

4000K

symmetric, medium beam [M]



Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
linear spread, medium beam [M]	134-6300+134-1382	LED-24/48W / 700 mA - 3000 K	5508.3	54 W	80	8.10
•	134-6301+134-1382	LED-24/48W / 700 mA - 4000 K	5888.1	54 W	80	8.10
symmetric, medium beam [M]	134-6300	LED-24/48W / 700 mA - 3000 K	6047.2	54 W	80	8.10
	134-6301	LED-24/48W / 700 mA - 4000 K	6464.2	54 W	80	8.10
symmetric, very narrow beam [VN]	134-6303	LED-24/48W / 700 mA - 3000 K	5986.1	54 W	80	8.10
	134-6304+134-1492	LED-24/48W / 700 mA - 4000 K	6398.9	54 W	80	8.10
symmetric, very narrow beam, 'sharp	134-6306	LED-24/48W / 700 mA - 3000 K	6442.7	54 W	80	8.10
cut-off' [VNS]	134-6307	LED-24/48W / 700 mA - 4000 K	6887	54 W	80	8.10
symmetric, wide beam [W]	134-6309	LED-24/48W / 700 mA - 3000 K	5388.5	54 W	80	8.10
	134-6310	LED-24/48W / 700 mA - 4000 K	5760.1	54 W	80	8.10
wallwash	134-6300+134-1492	LED-24/48W / 700 mA - 3000 K	5186.6	54 W	80	8.10
	134-6301+134-1492	LED-24/48W / 700 mA - 4000 K	5186.6	54 W	80	8.10



Optical Accessories

Honeycomb louvre


Description	Part ID	C1
IW-DOC24_LED	134-1445	7.52





Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC240-LED	134-1492	7.52



Linear spread lens

Description	Part ID	C1
IO-180-DAC/D	ED 134-1382	7.52

