
we-ef

Ceiling Luminaires





Description

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation over recessed junction box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



Ceiling Luminaires

Specifications Material description

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens, hinged

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP65
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	---

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h	
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.	

we-ef

Ceiling Luminaires

Options Light distribution



symmetric, wide beam [W]



symmetric, medium beam [M]



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



wallwash [A20]



linear spread, medium beam [M]

Color temperature Nominal Watt



3000 K



56 W



Ceiling Luminaires

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (lb)
linear spread, medium beam [M]	134-1433+134-1382	LED-24/48W / 700 mA - 3000 K	5508.3	54 W	80	16.80
•	134-1437+134-1382	LED-24/48W / 700 mA - 4000 K	5888.1	54 W	80	16.80
symmetric, medium beam [M]	134-1433	LED-24/48W / 700 mA - 3000 K	6047.2	54 W	80	16.80
	134-1437	LED-24/48W / 700 mA - 4000 K	6464.2	54 W	80	16.80
symmetric, very narrow beam [VN]	134-1434	LED-24/48W / 700 mA - 3000 K	5986.1	54 W	80	16.80
	134-1438	LED-24/48W / 700 mA - 4000 K	6398.9	54 W	80	16.80
symmetric, very narrow beam, 'sharp	134-1435+134-1382	LED-24/48W / 700 mA - 3000 K	6442.7	54 W	80	16.80
cut-off' [VNS]	134-1439	LED-24/48W / 700 mA - 4000 K	6887	54 W	80	16.80
symmetric, wide beam [W]	134-1432	LED-24/48W / 700 mA - 3000 K	5388.5	54 W	80	16.80
	134-1436+134-1382	LED-24/48W / 700 mA - 4000 K	5760.1	54 W	80	16.80
wallwash [A20]	134-1433+134-1492	LED-24/48W / 700 mA - 3000 K	4851.9	54 W	80	16.80
	134-1437+134-1492	LED-24/48W / 700 mA - 4000 K	5186.6	54 W	80	16.80



Ceiling Luminaires

Optical Accessories

Honeycomb louvre

Description	Part ID	C1
IW-DOC24_LED	134-1445	7.52




Wallwash lens



Ceiling Luminaires

ption Part ID C1
-WW-DAC/DOC240-LED 134-1492 7.52



Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC240-LED	134-1382	7.52



WE-EF LIGHTING USA, LLC

Ceiling Luminaires

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 Phone: +1 724 742 0030

> customersupport.usa@we-ef.com https://we-ef.com/us

Subject to technical changes and errors.

Generated on 10/23/2024

