**Description**

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation over recessed junction box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Ceiling Luminaires**Specifications****Material description**

Body	Marine-grade die-cast aluminium alloy
Lens	Safety glass lens, hinged
Colors	<div><div></div> RAL9004 Black</div> <div><div></div> RAL9007 Grey Metallic</div> <div><div></div> RAL9016 White</div> <div><div></div> RAL8019 Dark Bronze</div>
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP65
Impact resistance	IK07
Corrosion resistance	5CE

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030
customersupport.usa@we-ef.com - <https://we-ef.com/us>
Subject to technical changes and errors. - Generated on 07/24/2025

DAC240 LED

Ceiling Luminaires



Options

Light distribution



symmetric, wide beam [W]



symmetric, medium beam [M]



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



wallwash [A20]




linear spread, medium beam [M]

Color temperature



3000 K



4000K







Nominal Watt

56 W

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030
customersupport.usa@we-ef.com - <https://we-ef.com/us>
Subject to technical changes and errors. - Generated on 07/24/2025

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
linear spread, medium beam [M] 	134-1433+134-1382	LED-24/48W / 700 mA - 3000 K	5508.3	54 W	80	16.80
	134-1437+134-1382	LED-24/48W / 700 mA - 4000 K	5888.1	54 W	80	16.80
symmetric, medium beam [M] 	134-1433	LED-24/48W / 700 mA - 3000 K	6047.2	54 W	80	16.80
	134-1437	LED-24/48W / 700 mA - 4000 K	6464.2	54 W	80	16.80
symmetric, very narrow beam [VN] 	134-1434	LED-24/48W / 700 mA - 3000 K	5986.1	54 W	80	16.80
	134-1438	LED-24/48W / 700 mA - 4000 K	6398.9	54 W	80	16.80
symmetric, very narrow beam, 'sharp cut-off' [VNS] 	134-1435+134-1382	LED-24/48W / 700 mA - 3000 K	6442.7	54 W	80	16.80
	134-1439	LED-24/48W / 700 mA - 4000 K	6887	54 W	80	16.80
symmetric, wide beam [W] 	134-1432	LED-24/48W / 700 mA - 3000 K	5388.5	54 W	80	16.80
	134-1436+134-1382	LED-24/48W / 700 mA - 4000 K	5760.1	54 W	80	16.80
wallwash [A20] 	134-1433+134-1492	LED-24/48W / 700 mA - 3000 K	4851.9	54 W	80	16.80
	134-1437+134-1492	LED-24/48W / 700 mA - 4000 K	5186.6	54 W	80	16.80

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030


customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 07/24/2025

Optical Accessories

Softening Lens

Description	Part ID	C1
IO-360-DAC/DOC240-LED	134-1441	7.52



DAC240 LED



Ceiling Luminaires

Honeycomb louvre

Description	Part ID	C1
IW-DOC24_LED	134-1445	7.52



Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC240-LED	134-1492	7.52



DAC240 LED

Ceiling Luminaires



Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC240-LED	134-1382	7.52

